

Part Number	<b>VALVES STACK</b>	
	<b>SN - 4 - TAK - BOK SERIES</b>	
	<b>( 80 LITRES FLOW RATE 1/2" PORTS )</b>	
SN-4/1S-3/18L/P3T/G-4-6/M3	SN - 4 / 1 S - 3 / 1 8 L / G - 4 - 6 / M 3	ONE SPOOL
SN-4/2S-3/18L/P3T/G-4-6/M3	SN - 4 / 2 S - 3 / 1 8 L / G - 4 - 6 / M 3	TWO SPOOL
SN-4/3S-3/18L/P3T/G-4-6/M3	SN - 4 / 3 S - 3 / 1 8 L / G - 4 - 6 / M 3	THREE SPOOL
SN-4/4S-3/18L/P3T/G-4-6/M3	SN - 4 / 4 S - 3 / 1 8 L / G - 4 - 6 / M 3	FOUR SPOOL
SN-4/5S-3/18L/P3T/G-4-6/M3	SN - 4 / 5 S - 3 / 1 8 L / G - 4 - 6 / M 3	FIVE SPOOL
SN-4/6S-3/18L/P3T/G-4-6/M3	SN - 4 / 6 S - 3 / 1 8 L / G - 4 - 6 / M 3	SIX SPOOL
SN-4/7S-3/18L/P3T/G-4-6/M3	SN - 4 / 7 S - 3 / 1 8 L / G - 4 - 6 / M 3	SEVEN SPOOL
SN-4/8S-3/18L/P3T/G-4-6/M3	SN - 4 / 8 S - 3 / 1 8 L / G - 4 - 6 / M 3	EIGHT SPOOL
SN-4/9S-3/18L/P3T/G-4-6/M3	SN - 4 / 9 S - 3 / 1 8 L / G - 4 - 6 / M 3	NINE SPOOL
SN-4/10S-3/18L/P3T/G-4-6/M3	SN - 4 / 10 S - 3 / 1 8 L / G - 4 - 6 / M 3	TEN SPOOL
SN-4/11S-3/18L/P3T/G-4-6/M3	SN - 4 / 11 S - 3 / 1 8 L / G - 4 - 6 / M 3	ELEVEN SPOOL
SN-4/12S-3/18L/P3T/G-4-6/M3	SN - 4 / 12 S - 3 / 1 8 L / G - 4 - 6 / M 3	TWELVE SPOOL
	<b>POSSIBLE OPTIONS :</b>	
18 X 1.5 INHEX	POWER BEYOND <b>POSSIBLE</b> ; USE 18 X 1.5 METRIC INHEX PLUG	
4B-12 + DW-12	CLOSED CENTER <b>POSSIBLE</b> ; USE ABOVE & 3/4" BSPP HEX NUT ADAPTOR & WASHER	
	<b>SPOOL TYPE</b>	
YLWSN42001	SPOOL DOUBLE ACTING ON PORT ( A & B )	( SPOOL TYPE 1 )
YLWSN42002	SPOOL MOTOR ACTING ON PORT ( A & B )	( SPOOL TYPE 2 )
YLWSN42003	SPOOL SINGLE ACTING ON PORT ( A )	( SPOOL TYPE 3 ) ( SPOOL OUT ) LEVER IN
YLWSN42004	SPOOL SINGLE ACTING ON PORT ( B )	( SPOOL TYPE 4 ) ( SPOOL IN ) LEVER OUT
YLWSN45003	PORT RELIEF VALVES PER PORT P (G3-100) RANGE 100 TO 250 BAR	
YLWSN45004	PORT RELIEF VALVES PER PORT P (G4-200) RANGE 200 TO 315 BAR	
	<b>SPOOL CONTROL</b>	
YLWSN43061	3 POSITION DETENT KIT TYPE ( 6-1 )	
YLWSN43092	3 POSITION DETENT KIT TYPE ( 9-2 ) DETENTED PORT ( B ) ( SPOOL IN ) LEVER OUT	
YLWSN43093	3 POSITION DETENT KIT TYPE ( 9-3 ) DETENTED PORT ( A ) ( SPOOL OUT ) LEVER IN	
YLWSN43080	PNEUMATIC CONTROL KIT TYPE ( 8P )	
YLWSN430810	HYDRAULIC PILOT CONTROL KIT TYPE ( 8IM )	
YLWSN44002	JOYSTICK	KIT TYPE ( LCB )
YLWSN43082	DUAL CONTROL	KIT TYPE ( 8D2 )
	<b>ACCESSORIES</b>	
YLWSN44000	LEVER BOX	KIT TYPE ( L )
YLWSN44001	DUST CAP	KIT TYPE ( SPL )
YLWSN43008	END CAP	KIT TYPE ( 8 )
YLWSN10200	LEVER	KIT TYPE ( YLO1M10X200 )
YLPSN43003S	RELIEF VALVE SPRING	KIT TYPE ( DG-3 ) RANGE 63 - 200 BAR
YLPSN43004S	RELIEF VALVE SPRING	KIT TYPE ( DG-4 ) RANGE 160 - 315 BAR
	<b>TECHNICAL SPECIFICATIONS:</b>	
	P - PORT	1/2" BSPP
	A - PORT (SPRING)	1/2" BSPP
	B - PORT (LEVER)	1/2" BSPP
	T - PORT	3/4" BSPP
	CO - PORT	3/4" BSPP
	<b>RECOMMENDED FLOW RATE:</b>	
	80 LITRES PER MIN.	
	<b>MAX OPERATING PRESSURE:</b>	
	315 BAR	
	<b>PORT PRESSURE:</b>	
	315 BAR	
	<b>TANK LINE PRESSURE:</b>	
	25 BAR	

