

Part Number	VALVES STACK	
	<u>SN - 6 - TAK - BOK SERIES</u>	
	(150 LITRES FLOW RATE 3/4" PORTS)	
SN-6/1S-3/18L/P3T/G-6-1/M3	SN - 6 / 1 S - 3 / 1 8 L / G - 6 - 1 / M 3	ONE SPOOL
SN-6/2S-3/18L/P3T/G-6-1/M3	SN - 6 / 2 S - 3 / 1 8 L / G - 6 - 1 / M 3	TWO SPOOL
SN-6/3S-3/18L/P3T/G-6-1/M3	SN - 6 / 3 S - 3 / 1 8 L / G - 6 - 1 / M 3	THREE SPOOL
SN-6/4S-3/18L/P3T/G-6-1/M3	SN - 6 / 4 S - 3 / 1 8 L / G - 6 - 1 / M 3	FOUR SPOOL
SN-6/5S-3/18L/P3T/G-6-1/M3	SN - 6 / 5 S - 3 / 1 8 L / G - 6 - 1 / M 3	FIVE SPOOL
SN-6/6S-3/18L/P3T/G-6-1/M3	SN - 6 / 6 S - 3 / 1 8 L / G - 6 - 1 / M 3	SIX SPOOL
SN-6/7S-3/18L/P3T/G-6-1/M3	SN - 6 / 7 S - 3 / 1 8 L / G - 6 - 1 / M 3	SEVEN SPOOL
SN-6/8S-3/18L/P3T/G-6-1/M3	SN - 6 / 8 S - 3 / 1 8 L / G - 6 - 1 / M 3	EIGHT SPOOL
	<u>POSSIBLE OPTIONS :</u>	
18 X 1.5" INHEX	POWER BEYOND POSSIBLE ; USE 18 X 1.5 METRIC INHEX PLUG	
4B-16 + DW-16	CLOSED CENTER POSSIBLE ; USE ABOVE & 1" BSPP HEX NUT ADAPTOR & WASHER	
	<u>SPOOL TYPE</u>	
YLWSN62001	SPOOL DOUBLE ACTING ON PORT (A & B)	(SPOOL TYPE 1)
YLWSN62002	SPOOL MOTOR ACTING ON PORT (A & B)	(SPOOL TYPE 2)
YLWSN62003	SPOOL SINGLE ACTING ON PORT (A) (SPOOL TYPE 3) (SPOOL OUT) LEVER IN	
YLWSN62004	SPOOL SINGLE ACTING ON PORT (B) (SPOOL TYPE 4) (SPOOL IN) LEVER OUT	
YLWSN65003	PORT RELIEF VALVES PER PORT P (G3-100) RANGE 100 TO 250 BAR	
YLWSN65004	PORT RELIEF VALVES PER PORT P (G4-200) RANGE 200 TO 315 BAR	
	<u>SPOOL CONTROL</u>	
YLWSN63061	3 POSITION DETENT KIT TYPE (6-1)	
YLWSN63092	3 POSITION DETENT KIT TYPE (9-2) DETENTED PORT (B) (SPOOL IN) LEVER OUT	
YLWSN63093	3 POSITION DETENT KIT TYPE (9-3) DETENTED PORT (A) (SPOOL OUT) LEVER IN	
YLWSN63080	PNEUMATIC CONTROL KIT TYPE (8P)	
YLWSN630810	HYDRAULIC PILOT CONTROL KIT TYPE (8IM)	
YLWSN64002	JOYSTICK	KIT TYPE (LCB)
YLWSN63082	DUAL CONTROL	KIT TYPE (8D2)
YLWSN		
	<u>ACCESSORIES</u>	
YLWSN64000	LEVER BOX	KIT TYPE (L)
YLWSN64001	DUST CAP	KIT TYPE (SPL)
YLWSN63008	END CAP	KIT TYPE (8)
YLWSN10200	LEVER	KIT TYPE (YLO1M10X200)
YLPSN63002S	RELIEF VALVE SPRING	KIT TYPE (DG-3) RANGE 63 - 200 BAR
YLPSN63003S	RELIEF VALVE SPRING	KIT TYPE (DG-4) RANGE 160 - 315 BAR
YLPSN63000	PILOT OPERATED RELIEF	KIT TYPE (XFG) RANGE 25 - 315 BAR
	<u>TECHNICAL SPECIFICATIONS:</u>	
	P - PORT	3/4" BSPP
	A - PORT (SPRING)	3/4" BSPP
	B - PORT (LEVER)	3/4" BSPP
	T - PORT	1" BSPP
	CO - PORT	1" BSPP
	<u>RECOMMENDED FLOW RATE:</u>	
	150 LITRES PER MIN.	
	<u>MAX OPERATING PRESSURE:</u>	
	315 BAR	
	<u>PORT PRESSURE:</u>	
	315 BAR	
	<u>TANK LINE PRESSURE:</u>	
	25 BAR	

