

MOTORS GEROLOR TAK - BOK

<u>Part Number</u>								
	<u>BMM SERIES</u>		16mm SHAFT 3-1/4" SPIGOT 2 BOLT MOUNT					
	COMPETITOR MODELS (OMM - DANFOSS) (EPMM - M&S) (J - CHAR - LYNN)							

	Type	cc/rev	Cont. Speed	Cont. Flow	Cont. Press Drop	Cont. Torque	Cont. Kw	Rotor Height
45 BMM -12-F-A-1E	BMM	12	1550 rpm	20 L	100 bar	16 Nm	2.4	5.5 mm
45 BMM- 20-F-A-1E	BMM	20	1000 rpm	20 L	100 bar	25 Nm	2.4	8.5 mm
45 BMM- 32-F-A-1E	BMM	32	630 rpm	20 L	100 bar	40 Nm	2.4	13.5 mm
45 BMM -40-F-A-1E	BMM	40	500 rpm	20 L	90 bar	45 Nm	2.2	17 mm
45 BMM -50-F-A-1E	BMM	50	400 rpm	20 L	70 bar	46 Nm	1.8	21 mm

<u>OPTIONS</u>	
44 BMM -XX-X-X-1E	CODE FOR REAR PORTS 3/8" BSPP
45 BMM -XX-X-X-E	CODE FOR SIDE PORTS 3/8" BSPP
46 BMM -XX-F-X-X	CODE FOR 2 BOLT FLANGE 63mm SPIGOT
46 BMM -XX-U-X-X	CODE FOR 3 BOLT MOUNT 31.5mm SPIGOT
45 BMM -XX-X-A-X	CODE FOR SHAFT P/KEY 16mm O/D
46 BMM -XX-X-C-X	CODE FOR SHAFT 9 SPLINE 16.5mm O/D

<u>MOTOR DATA</u>							
	TYPE	SPIGOT	MOUNT	SHAFT	PORTS	DRAIN	
45 BMM-XX-F-A-1E	BMM GEROTOR	63mm	2	16mm P/K	3/8"BSPP	1/8"BSPP	

<u>BRAKE DATA</u>							
	TYPE	SPIGOT	MOUNT	SHAFT	Min Static Torque	Min Opening Pressure	Max Open Pressure
45 ZD-Q-2	ZD-2-Q	3-1/4"	4 BOLT	25mm	410-450	17-23Bar	300Bar



BMM-16-U-A-1E



ZD-Q-2