

Part Number	VALVES MONOBLOCK	
	<u>MB - 4 - TAK - BOK SERIES</u>	
	(60 LITRES FLOW RATE 1/2" PORTS)	
MB-4/1-S-3/18L/G-4/M3	MB - 4 / 1 - S - 3 / 1 8 L / G - 4 / M 3	ONE SPOOL
MB-4/2-S-3/18L/G-4/M3	MB - 4 / 2 - S - 3 / 1 8 L / G - 4 / M 3	TWO SPOOL
MB-4/3-S-3/18L/G-4/M3	MB - 4 / 3 - S - 3 / 1 8 L / G - 4 / M 3	THREE SPOOL
MB-4/4-S-3/18L/G-4/M3	MB - 4 / 4 - S - 3 / 1 8 L / G - 4 / M 3	FOUR SPOOL
MB-4/5-S-3/18L/G-4/M3	MB - 4 / 5 - S - 3 / 1 8 L / G - 4 / M 3	FIVE SPOOL
MB-4/6-S-3/18L/G-4/M3	MB - 4 / 6 - S - 3 / 1 8 L / G - 4 / M 3	SIX SPOOL
	<u>POSSIBLE OPTIONS</u>	
4NN-04	POWER BEYOND POSSIBLE ; USE 1/4" NPT INHEX PLUG	
4B-08 + DW-08	CLOSED CENTER POSSIBLE ; USE ABOVE & 1/2" BSPP HEX NUT ADAPTOR & WASHER	
	<u>SPOOL TYPE</u>	
YLMB43001	SPOOL DOUBLE ACTING ON PORT (A & B) (SPOOL TYPE 1)	
YLMB43002	SPOOL MOTOR ACTING ON PORT (A & B) (SPOOL TYPE 2)	
YLMB43003	SPOOL SINGLE ACTING ON PORT (A) (SPOOL TYPE 3) (SPOOL IN) LEVER OUT	
YLMB43004	SPOOL SINGLE ACTING ON PORT (B) (SPOOL TYPE 4) (SPOOL OUT) LEVER IN	
	<u>SPOOL CONTROL</u>	
YLMB44061	3 POSITION DETENT KIT TYPE (6-1)	
YLMB44092	3 POSITION DETENT KIT TYPE (9-2) DETENTED PORT (A) (SPOOL IN) LEVER OUT	
YLMB44093	3 POSITION DETENT KIT TYPE (9-3) DETENTED PORT (B) (SPOOL OUT) LEVER IN	
YLMB44080	PNEUMATIC CONTROL KIT TYPE (8P)	
YLMB45002	JOYSTICK KIT TYPE (LCB)	
YLMB44200	DUAL CONTROL KIT TYPE (8D2)	
	<u>ACCESSORIES</u>	
YLMB45000	LEVER BOX KIT TYPE (L)	
YLMB44008	END CAP KIT TYPE (8)	
YLMB45001	DUST CAP KIT TYPE (SPL)	
YLMB08160	LEVER KIT TYPE (YLO2M8X160)	
YLMB42002S	RELIEF VALVE SPRING KIT TYPE (DG-2) RANGE 40 - 80 BAR	
YLMB42003S	RELIEF VALVE SPRING KIT TYPE (DG-3) RANGE 63 - 200 BAR	
YLMB42004S	RELIEF VALVE SPRING KIT TYPE (DG-4) RANGE 160 - 315 BAR	
	<u>TECHNICAL SPECIFICATIONS</u>	
	<u>THREADS AND SIZES:</u>	
	A - PORT ON TOP	1/2" BSPP
	B - PORT ON TOP	1/2" BSPP
	P - PORT ON TOP	1/2" BSPP
	T - PORT ON TOP	1/2" BSPP
	C/O - PORT ON SIDE	1/2" BSPP
	<u>RECOMMENDED FLOW RATE:</u>	
	60 LITRES PER MIN.	
	<u>PRESET OPERATING PRESSURE:</u>	
	120 BAR	
	<u>MAXIMUM OPERATING PRESSURE:</u>	
	315 BAR	
	<u>TANK LINE PRESSURE:</u>	
	25 BAR	
	<u>PORT IDENTIFICATION</u>	
	PORT (B) CLOSEST TO SPRING	
	PORT (A) CLOSEST TO LEVER	

